

Model Name

MH856UST Digital Projector

Unique selling point

Trade Mark

- * Ultra short throw with 1080p image quality
- * Dual HDMI port. Support MHL.
- * Optional PointWrite interactive capability
- * Cornor fit adjustment
- * Wall mount bundle





Projection System	DLP							
Vative Resolution	1080p(1920*1080)							
Brightness	3500AL							
Contrast Ratio	10,000:1							
Display Color	1.07 Billion Colors							
ens	F2.5,f=5.1mm							
Aspect Ratio	Native 16:9 (6 aspect ratio selectable)							
hrow Ratio	0.33							
Clear Image Size/Max Image size	88.9"~110/300"							
Loom Ratio	Fix							
amp Type	280W							
.amp(Normal/Economic/SmartEco Mode) [*]	3000/4000/7000 hours							
Keystone Adjustment	2D, Vertical/Horizontal +/- 30 degrees							
Projection Offset	150%(±5%)							
Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)							
lorizontal Frequency	15~102KHz							
/ertical Scan Rate	23~120Hz							
Compatibility	HDTV Compatibility	480i, 480p, 5	76i, 576p, 720p, 1080i, 1080p					
	Video Compatibility	NTSC, PAL, S						
nterface	Computer in (D-sub 15pin)	× 2(Shared with component)						
	Monitor out (D-sub 15pin)		xl					
	Composite Video in (RCA)		xl					
	S-Video in (Mini DIN 4pin)		×I					
	HDMI/MHL		x 2(HDMI I with MHL)					
	Audio in (Mini Jack)		x I					
			x I					
	Audio out (Mini Jack)		x I					
	Audio L/R		x I 10W x 2					
	Speaker		x I (PointWrite interactive module)					
	USB (Type mini B)		x I (Pointwrite interactive module) xI (FW download)					
	USB (Type B)		x1 (FVV download) x1 (5V 2A Power for PT02 Touch module)					
	USB(Type A)							
	RJ45		xI (LAN control)					
			x I					
	RS232 (DB-9pin)							
	RS232 (DB-9pin) IR Receiver		xI (Front)					
limensions	IR Receiver		x1 (Front) 373.3*287.5*130.2mm (w/c	· · · · · · · · · · · · · · · · · · ·				
Dimensions	· · · /		xI (Front)	· · · · · · · · · · · · · · · · · · ·				
Dimensions	IR Receiver		x1 (Front) 373.3*287.5*130.2mm (w/c	· · · · · · · · · · · · · · · · · · ·				
Dimensions Yower	IR Receiver Dimensions(W x H x D)		x1 (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir	ror)				
	IR Receiver Dimensions(W x H x D) Weight		x1 (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir 5KG(w/o wall mount)	ror) Hz				
	IR Receiver Dimensions(W x H x D) Weight Power Supply	de)	x1 (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir 5KG(w/o wall mount) AC100 to 240 V, 50 to 60	ror) Hz				
'ower	IR Receiver Dimensions(W x H x D) Weight Power Supply Power Consumption 37/33 dBA (Normal/Economic mod		x1 (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir 5KG(w/o wall mount) AC100 to 240 V, 50 to 60 typical 380W, stanby powe	ror) Hz r <0.5W				
'ower Audible Noise	IR Receiver Dimensions(W x H x D) Weight Power Supply Power Consumption 37/33 dBA (Normal/Economic mod Arabic/Bulgarian/ Croatian/ Czech/	/ Danish/ Dutch/ E	x1 (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir 5KG(w/o wall mount) AC100 to 240 V, 50 to 60 typical 380W, stanby powe	ror) Hz r <0.5W / Greek/ Hindi/ Hungarian/				
'ower Audible Noise	IR Receiver Dimensions(W x H x D) Weight Power Supply Power Consumption 37/33 dBA (Normal/Economic mod Arabic/Bulgarian/ Croatian/ Czech/ Italian/ Indonesian/ Japanese/ Korea	/ Danish/ Dutch/ E an/ Norwegian/ Po	x1 (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir 5KG(w/o wall mount) AC100 to 240 V, 50 to 60 typical 380W, stanby powe	ror) Hz r <0.5W / Greek/ Hindi/ Hungarian/				
'ower Audible Noise	IR Receiver Dimensions(W x H x D) Weight Power Supply Power Consumption 37/33 dBA (Normal/Economic mod Arabic/Bulgarian/ Croatian/ Czech/	/ Danish/ Dutch/ E an/ Norwegian/ Po	x1 (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir 5KG(w/o wall mount) AC100 to 240 V, 50 to 60 typical 380W, stanby powe	ror) Hz r <0.5W / Greek/ Hindi/ Hungarian/				
'ower Audible Noise	IR Receiver Dimensions(W x H x D) Weight Power Supply Power Consumption 37/33 dBA (Normal/Economic mod Arabic/Bulgarian/ Croatian/ Czech/ Italian/ Indonesian/ Japanese/ Korea	/ Danish/ Dutch/ E an/ Norwegian/ Po	x1 (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir 5KG(w/o wall mount) AC100 to 240 V, 50 to 60 typical 380W, stanby powe	ror) Hz r <0.5W / Greek/ Hindi/ Hungarian/				
Power Audible Noise Dn-Screen Display Languages	IR Receiver Dimensions(W x H x D) Weight Power Supply Power Consumption 37/33 dBA (Normal/Economic mod Arabic/Bulgarian/ Croatian/ Czech/ Italian/ Indonesian/ Japanese/ Korea Chinese/Spanish/ Swedish/ Turkish	/ Danish/ Dutch/ E an/ Norwegian/ Po	x1 (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201 mm(w Mir 5KG(w/o wall mount) AC100 to 240 V, 50 to 60 typical 380W, stanby powe nglish/ Finnish/ French/ Germann lish/ Portuguese/ Romanian/ Rus Chinese (28 Languages)	ror) Hz r <0.5W / Greek/ Hindi/ Hungarian/				
Power Audible Noise Dn-Screen Display Languages	IR Receiver Dimensions(W x H x D) Weight Power Supply Power Consumption 37/33 dBA (Normal/Economic mod Arabic/Bulgarian/ Croatian/ Czech/ Italian/ Indonesian/ Japanese/ Korea Chinese/Spanish/ Swedish/ Turkish Standard	/ Danish/ Dutch/ Ei an/ Norwegian/ Po / Thai/ Traditional	x1 (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir 5KG(w/o wall mount) AC100 to 240 V, 50 to 60 typical 380W, stanby powe nglish/ Finnish/ French/ German lish/ Portuguese/ Romanian/ Rus Chinese (28 Languages) Optional	ror) Hz r <0.5W / Greek/ Hindi/ Hungarian/				
Power Audible Noise Dn-Screen Display Languages	IR Receiver Dimensions(W × H × D) Weight Power Supply Power Consumption 37/33 dBA (Normal/Economic mod Arabic/Bulgarian/ Croatian/ Czech/ Italian/ Indonesian/ Japanese/ Korea Chinese/Spanish/ Swedish/ Turkish Standard Remote Control w/ Battery	/ Danish/ Dutch/ Ei an/ Norwegian/ Po / Thai/ Traditional RCS011	x1 (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir 5KG(w/o wall mount) AC100 to 240 V, 50 to 60 typical 380W, stanby powe nglish/ Finnish/ French/ Germand lish/ Portuguese/ Romanian/ Rus Chinese (28 Languages) Optional Spare Lamp Kit	ror) Hz r <0.5W ' Greek/ Hindi/ Hungarian/ ssian/ Simplified				
Power Audible Noise Dn-Screen Display Languages	IR Receiver Dimensions(W × H × D) Weight Power Supply Power Consumption 37/33 dBA (Normal/Economic mod Arabic/Bulgarian/ Croatian/ Czech/ Italian/ Indonesian/ Japanese/ Korea Chinese/Spanish/ Swedish/ Turkish Standard Remote Control w/ Battery Power Cord (by region)	/ Danish/ Dutch/ Ei an/ Norwegian/ Po / Thai/ Traditional RCS011 2.9M	x1 (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir 5KG(w/o wall mount) AC100 to 240 V, 50 to 60 typical 380W, stanby powe nglish/ Finnish/ French/ Germann lish/ Portuguese/ Romanian/ Rus Chinese (28 Languages) Optional Spare Lamp Kit Wall Mount	ror) Hz r <0.5W ' Greek/ Hindi/ Hungarian/ ssian/ Simplified				
Power Audible Noise Dn-Screen Display Languages	IR Receiver Dimensions(W × H × D) Weight Power Supply Power Consumption 37/33 dBA (Normal/Economic model) Arabic/Bulgarian/ Croatian/ Czech/ Italian/ Indonesian/ Japanese/ Koree Chinese/Spanish/ Swedish/ Turkish Standard Remote Control w/ Battery Power Cord (by region) User Manual CD Quick Start Guide	/ Danish/ Dutch/ Ei an/ Norwegian/ Po / Thai/ Traditional RCS011 2.9M *1	x I (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir 5KG(w/o wall mount) AC100 to 240 V, 50 to 60 typical 380W, stanby powe nglish/ Finnish/ French/ Germann lish/ Portuguese/ Romanian/ Rus Chinese (28 Languages) Optional Spare Lamp Kit Wall Mount 3D Glasses	ror) Hz r <0.5W / Greek/ Hindi/ Hungarian/ ssian/ Simplified WM04G4 DGD24				
Power Audible Noise Dn-Screen Display Languages	IR Receiver Dimensions(W × H × D) Weight Power Supply Power Consumption 37/33 dBA (Normal/Economic mod Arabic/Bulgarian/ Croatian/ Czech/ Italian/ Indonesian/ Japanese/ Kore: Chinese/Spanish/ Swedish/ Turkish Standard Remote Control w/ Battery Power Cord (by region) User Manual CD	/ Danish/ Dutch/ Ei an/ Norwegian/ Po / Thai/ Traditional RCS011 2.9M *1 *1	x I (Front) 373.3*287.5*130.2mm (w/c 373.3*287.5*201mm(w Mir 5KG(w/o wall mount) AC100 to 240 V, 50 to 60 typical 380W, stanby powe nglish/ Finnish/ French/ Germann lish/ Portuguese/ Romanian/ Rus Chinese (28 Languages) Optional Spare Lamp Kit Wall Mount 3D Glasses Document Camera	ror) Hz r <0.5W / Greek/ Hindi/ Hungarian/ ssian/ Simplified WM04G4 DGD24 S30				


*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

MH856UST Digital Projector


Distance Chart

MH856UST The screen aspect ratio is 16:9 and the projected picture is 16:9.

1080P											
Screen size (Diagonal)		Screen width (VV)		Screen height (H)		Projection distance (D)		Offset (H)		Distance between Wall plate & projection screen	
inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	· · (V)	
89	2258	77.5	1968	43.6	1107	13.40	340.3	13.04	331.2	273	
90	2286	78.4	1991	44.1	1120	13.73	348.8	13.17	334.5	277	
95	2413	82.8	2103	46.6	1183	15.35	389.8	13.80	350.5	294	
97	2464	84.5	2148	47.6	1208	15.98	405.8	14.04	356.7	300	
100	2540	87.1	2213	49	1245	16.94	430.3	14.42	366.2	309	
102	2594	89.1	2262	50.1	1272	17.65	448.3	14.70	373.3	319	



Wall mount/Ceiling mount Chart



Dimension





BenQ Scalable Interaactive System

BenQ PointWrite interactive projectors turn any surface into an interactive whiteboard by utilizing an innovative infrared technology to detect transmitter light emitted from the PointWrite Pen or touch module that enable the camera to detect the finger or object movements. This allows teachers to invite students up to the board to make notes, answer questions, or collaborate on digital paintings, sparking creativity, imagination and lots of fun. Easy to set up and flexible to use, these education projectors make a cost-efficient and affordable option for every classroom.

Key features

- Compatible with series BenQ short throw and ultra-short throw projector
- Supports up to 4 pens/fingers
- Dual screen tuoch for ultra wide working space.
- Effortless setup with only I second auto calibration*
- An ultra-fast 0.016-second response time for a smooth writing experience *Calibration speed may vary depending on computer system.



Scalable dual screen and finger touch



