

MS506

Projection System	DLP
Native Resolution	SVGA (800 x 600)
Brightness*	3200 lumens
Contrast Ratio	13000:1
Display Color	1.07 Billion Colors
Lens	F=2.56-2.8, f=21-23.1mm
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)
Throw Ratio	1.86-2.04 (53" @ 2m)
Image Size (Diagonal)	60"-120"/ 300' (Clear Focus/ Maximum)
Zoom Ratio	1.1:1 (Powered)
Keystone Adjustment	1D, Vertical +/- 40 degrees
Projection Offset	120% ±5%
Resolution Support	VGA (640 x 480) to UXGA (1600 x 1200)
Horizontal Frequency	15K-102KHz
Vertical Scan Rate	23-120Hz
Interface	Computer In (D-sub 15pin) x 2 (Share with component) Monitor Out (D-sub 15pin) x 1 Composite Video In (RCA) x 1 S-Video In (Mini DIN 4pin) x 1 Audio In (Mini Jack) x 1 Audio Out (Mini Jack) x 1 Speaker 2W x 1 USB (Type mini B) x 1 (Download & Page/down) RS232 (DB-9pin) x 1 IR Receiver x 1 (Front)
Dimensions(W x H x D)	283 x 95 x 222mm (include feet) 283 x 88.7 x 222mm (exclude feet)
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Weight	1.8kg
Audible Noise	33/ 28 dBA (Normal/ Economic mode)
Power Supply	AC100 to 240V, 50 to 60Hz
Power Consumption	Normal 270W, Eco 220W, Standby < 0.5W
On-Screen Display Languages	Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)
Picture Modes	Dynamic/ Presentation/ sRGB/ Cinema/ User 1/ User 2 Remote Control w/ Battery Power Cord (by region)
Accessories (Standard)	Quick Start Guide Warranty Card (by region) VGA (D-sub 15pin) Cable Spare Lamp Kit
Accessories (Optional)	Ceiling Mount 3D Glasses Carry Bag
3D Support and Compatibility	Frame Sequential: Up to 720p 60Hz (Video), Up to WXGA 120Hz (PC Timing) Side by Side: Up to 1680 x 1050 60Hz (PC Timing) Top Bottom: Up to 1680 x 1050 60Hz (PC Timing)