

ML1500e

Ultra-slim portable LED Projector

- "PC-free" viewing Built in media player and office viewer
- 6W Stereo audio with SRS WOW HD audio processing
- Optional Wireless
- Slim & Lightweight 1.4kg



ML1500e

Introducing the all new ML1500e ultra-slim portable LED projector. This powerful, lightweight and portable projector projects vibrant HD ready images up to an impressive 100". Weighing only 1.4kg and supplied with a carry bag you can easily transport it between meetings.

Packed full of features the ML1500e incorporates a media player, native office viewer and built-in speakers with SRS WOW audio processing. It also includes an SD card slot, USB connection and optional wireless capabilities providing you with ultimate flexibility. Perfect for viewing Microsoft Office & Adobe PDF files, photos and videos.

Using the latest "Lamp-free" technology for exceptional colour fidelity, reliability and longevity, the Optoma LED ultra-slim portable projector is your perfect entertainment and business partner.

Media Player and Native Office Viewer

Play videos, photos, Microsoft Office* & Adobe PDF files directly from an SD card or USB stick and view them directly on the projector without the need to connect the projector to a laptop, PC or DVD player. *powerpoint animations not supported







Wireless Presentations

Present from your phone or tablet using the free App: MirrorOp Presenter. Available for both Android and iOS devices, MirrorOp Presenter gives you the freedom to wirelessly share and present documents and photos stored on your mobile device. Creating a more connected and collaborative experience for everyone.

Instantly connect and display presentation material wirelessly from a PC, Mac or mobile device using the optional mini WiFi dongle which connects discreetly to the USB port on your ML1500e, bringing you seamless wireless connectivity in a highly portable package. Enjoy big-screen presentations streamed to your projector, cable-free.

Audio WOW - SRS Wow HD™ Surround Sound

Embrace the WOW factor with SRS WOW HD surround sound audio processing to create a more natural audio experience with a deep, rich bass response. Easy to set up without the need for costly external speakers the ML1500e offers exceptional sound quality with on-board 6W stereo audio.

SRS WOW HD Features

- Stereo enhancement which improves dynamic audio performance
- Sculpted bass response for maximum thump from the onboard speakers
- More natural audio with a wider sound field

Ultra-Slim


Weighing only 1.4kg, the ML1500e is ultra light and slim. Coupled with the included carry case make it ideal for presentations on the go.



Auto Keystone

Digital keystone correction helps ensure that the projected image will always fit the area on which you are projecting.





3D Ready

Using the inherent speed of DLP® technology, Optoma 3D Ready projectors can output video and images at an astonishing rate of 120Hz, allowing you to show full screen, full colour, stereoscopic 3D. Useful for both professionals



and educators alike, the ML1500e brings both teaching and design to a whole new level of immersion and excitement.

Colour Guarantee

We are so confident that the ML1500e image colour quality will remain as good as the day you bought it that Optoma will guarantee it for five years.





Photos

Insert the SD card straight from your phone or camera to instantly share memories with small or large groups, without the need for extra cables. Alternatively leave a slideshow with audio running in the background before kicking off a meeting, to whet your audiences' appetite and stimulate discussion.

Videos

Sit back after a long day to enjoy your favourite movies... without the need for file conversion; the ML1500e directly supports all the most popular video & music file formats and being both HD-Ready and LED, you can also be sure of vibrant colours, depth and clarity that will not disappoint.

Presentation and Documents

With native support for Microsoft Office and Adobe PDF files, you can simply save your work onto an SD card* or USB memory stick* and you are ready to go.










*SD Card & USB memory stick not included. Connection to some devices may require additional cables, available separately. Supports up to 32GB.

LED Technology

Powered by LED's, the ML1500e delivers a wide colour gamut, superior colour saturation and outstanding brightness using separate Red, Blue and Green LEDs to produce intense yet accurate colours.


In many situations the perceived brightness of LED projectors can be up to twice the brightness of an equivalent lamp-based projector. LED brightness* specifications allow for a better comparison against lamp-based projectors, which do not take advantage of the enhanced brightness perception the Helmholtz-Kohlrausch (HK) effect creates.

Finally, the lamp-less LED illumination engine that powers the ML1500e does not require the inconvenience and cost of frequent lamp changes to maintain its optimal performance. It also doesn't need lengthy warm-up and cool down cycles before and after every viewing due to its almost instant start up and shut down times.




Instant On/Off

Quickly setup and pack up with instant power On/Off. LED technology allows the projector to be a full brightness in seconds.



Digital Signage

Built-in digital signage function. Perfect for digital signage applications such as advertising and museum demos.







We know that improving our products is the best way to reduce our impact on the environment. That's why at Optoma, we design our products to have a long usable life, use fewer materials, ship with the minimum packaging and be free of all possible toxic substances. Naturally, energy efficiency and being recyclable are built in at the design stage. With each new product, we strive towards minimising our environmental impact.


ML1500e Specification

Video Compatibility PAL, NTSC M/J, 3.58MHz, 4.43MHz, 480i, 480p, 576i, 576p, 720p, 1080i Displayable Colours 1073.4 Million Projection Lens F71.5; f=13.92mm, Fixed Throw Ratio 1.4:1 Projection Screen Size 0.43 - 2.54m (17" - 100") Diagonal 16:10 Projection Distance 0.52 - 3.00 metres Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 105% Horizonal Scan Rate 49.64 kHz Vertical Scan Rate 50 - 120 Hz Lamp Type LED Lamp Life² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40" Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Cusply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby) Operating Conditions 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Uniformity 85 % Security Kensington lock Standard Accessories Carry bag, AC power cord, HDMI cable, remote control, battery, quick start card Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount	Display Technology	Single 0.45" WXGA DMD Chip DLP® Technology by Texas Instruments				
Contrast 20,000:1 Noise Level (Eco mode) 30dB Weight (kg) 1.4 I/O Connectors HDMI, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, SD card slot, 2 x USB-A reader/wireless, micro US Video Compatibility PAL, NTSC M/J, 3.58MHz, 4.43MHz, 480i, 480p, 576i, 576p, 720p, 1080i Displayable Colours 1073.4 Million Projection Lens F/1.5; f=13.92mm, Fixed Throw Ratio 1.4:1 Projection Screen Size 0.43 - 2.54m (17" - 100") Diagonal 16:10 Projection Distance 0.52 - 3.00 metres Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 105% Horizontal Scan Rate 49.64 kHz Vertical Scan Rate 49.64 kHz Vertical Scan Rate 50 - 120Hz Lamp Type LED Lamp Life ² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40" Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Consumption 145W Bright mode (< 0.5W Standby) Operating Conditions 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Uniformity 85% Security Kensington lock Standard Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount	Native Resolution	WXGA 1280 x 800				
Noise Level (Eco mode) 30dB Weight (kg) 1.4 I/O Connectors HDMI, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, SD card slot, 2 x USB-A reader/wireless, micro US Video Compatibility PAL, NTSC M/J, 3.58MHz, 4.43MHz, 480i, 480p, 576i, 576p, 720p, 1080i Displayable Colours 1073.4 Million Projection Lens F1.5; f=13.92mm, Fixed Throw Ratio 1.4:1 Projection Screen Size 0.43 - 2.54m (17° - 100°) Diagonal 16:10 Projection Distance 0.52 - 3.00 metres Aspect Ratio 18:10 Native, 16:9/4:3 Compatible Offset 105% Horizontal Scan Rate 49.64 kHz Vertical Scan Rate 50 - 120Hz Lamp Life ² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40° Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Consumption 145W Bright mode (< 0.5W Standby) Operating Conditions 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Uniformity 85% Security Kensington lock Standard Accessories Carry bag, AC power cord, HDMI cable, remote con	Brightness ¹ (Bright Mode)	1500 LED Brightness*				
Weight (kg)	Contrast	20,000:1				
I/O Connectors	Noise Level (Eco mode)	30dB				
Video Compatibility PAL, NTSC M/J, 3.58MHz, 4.43MHz, 480i, 480p, 576i, 576p, 720p, 1080i Displayable Colours 1073.4 Million Projection Lens F/1.5; f=13.92mm, Fixed Throw Ratio 1.4:1 Projection Screen Size 0.43 - 2.54m (17" - 100") Diagonal 16:10 Projection Distance 0.52 - 3.00 metres Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 105% Horizontal Scan Rate 49.64 kHz Vertical Scan Rate 50 - 120Hz Lamp Type LED Lamp Life² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40° Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby)	Weight (kg)	1.4				
Displayable Colours 1073.4 Million Projection Lens F71.5; f=13.92mm, Fixed Throw Ratio 1.4:1 Projection Screen Size 0.43 - 2.54m (17" - 100") Diagonal 16:10 Projection Distance 0.52 - 3.00 metres Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 105% Horizontal Scan Rate 49.64 kHz Vertical Scan Rate 50 - 120Hz Lamp Type LED Lamp Life ² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40° Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby)	I/O Connectors	HDMI, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, SD card slot, 2 x USB-A reader/wireless, micro USB				
Projection Lens F/1.5; f=13.92mm, Fixed Throw Ratio 1.4:1 Projection Screen Size 0.43 - 2.54m (17" - 100") Diagonal 16:10 Projection Distance 0.52 - 3.00 metres Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 105% Horizontal Scan Rate 49.64 kHz Vertical Scan Rate 50 - 120Hz Lamp Type LED Lamp Life² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40° Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby)	Video Compatibility					
Throw Ratio 1.4:1 Projection Screen Size 0.43 - 2.54m (17" - 100") Diagonal 16:10 Projection Distance 0.52 - 3.00 metres Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 105% Horizontal Scan Rate 49.64 kHz Vertical Scan Rate 50 - 120Hz Lamp Type LED Lamp Life² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40" Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby)	Displayable Colours	1073.4 Million				
Projection Screen Size 0.43 - 2.54m (17" - 100") Diagonal 16:10 Projection Distance 0.52 - 3.00 metres Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 105% Horizontal Scan Rate 49.64 kHz Vertical Scan Rate 50 - 120Hz Lamp Type LED Lamp Life² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40° Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby) Operating Conditions 5 - 35° C, 85% Humidity (Max), 2500m Altitude (Max) Uniformity 85% Security Kensington Lecus Market 100 Pilon Ration Pilon Ration Ration Pilon Ration Ra	Projection Lens	F/1.5; f=13.92mm, Fixed				
Projection Distance Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 105% Horizontal Scan Rate 49.64 kHz Vertical Scan Rate 50 − 120Hz Lamp Type LED Lamp Life² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40° Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Supply Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby) Operating Conditions 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Uniformity 85 % Security Kensington lock Standard Accessories Carry bag, AC power cord, HDMI cable, remote control, battery, quick start card Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount RoHS	Throw Ratio					
Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 105% Horizontal Scan Rate 49.64 kHz Vertical Scan Rate 50 − 120Hz Lamp Type LED Lamp Life² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40° Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby)	Projection Screen Size	0.43 - 2.54m (17" - 100") Diagonal 16:10				
Offset 105% Horizontal Scan Rate 49.64 kHz Vertical Scan Rate 50 − 120Hz Lamp Type LED Lamp Life² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40° Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby) Operating Conditions 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Uniformity 85 % Security Kensington lock Standard Accessories Carry bag, AC power cord, HDMI cable, remote control, battery, quick start card Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount RoHS Compliant	Projection Distance	0.52 - 3.00 metres				
Horizontal Scan Rate 49.64 kHz Vertical Scan Rate 50 – 120Hz Lamp Type LED Lamp Life² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40° Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby) Operating Conditions 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Uniformity 85 % Security Kensington lock Standard Accessories Carry bag, AC power cord, HDMI cable, remote control, battery, quick start card Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount RoHS Compliant	Aspect Ratio	16:10 Native, 16:9/4:3 Compatible				
Vertical Scan Rate 50 – 120Hz Lamp Type LED Lamp Life² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40° Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby) Operating Conditions 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Uniformity 85 % Security Kensington lock Standard Accessories Carry bag, AC power cord, HDMI cable, remote control, battery, quick start card Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount RoHS Compliant	Offset	105%				
Lamp TypeLEDLamp Life² Bright20,000 hours LED Life (hrs)Keystone Correction±40° Vertical (Auto)Dimensions (W x D x H) (mm)270 x 170 x 42Power Supply100-240V, 50-60 HzPower Consumption145W Bright mode (< 0.5W Standby)	Horizontal Scan Rate	49.64 kHz				
Lamp Life² Bright 20,000 hours LED Life (hrs) Keystone Correction ±40° Vertical (Auto) Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby)	Vertical Scan Rate	50 – 120Hz				
Keystone Correction±40° Vertical (Auto)Dimensions (W x D x H) (mm)270 x 170 x 42Power Supply100-240V, 50-60 HzPower Consumption145W Bright mode (< 0.5W Standby)	Lamp Type	LED				
Dimensions (W x D x H) (mm) 270 x 170 x 42 Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby)	Lamp Life ² Bright	20,000 hours LED Life (hrs)				
Power Supply 100-240V, 50-60 Hz Power Consumption 145W Bright mode (< 0.5W Standby)	Keystone Correction	±40° Vertical (Auto)				
Power Consumption 145W Bright mode (< 0.5W Standby)	Dimensions (W x D x H) (mm)	270 x 170 x 42				
Operating Conditions 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Uniformity 85 % Security Kensington lock Standard Accessories Carry bag, AC power cord, HDMI cable, remote control, battery, quick start card Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount RoHS Compliant	Power Supply	100-240V, 50-60 Hz				
Uniformity 85 % Security Kensington lock Standard Accessories Carry bag, AC power cord, HDMI cable, remote control, battery, quick start card Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount RoHS Compliant	Power Consumption					
Security Kensington lock Standard Accessories Carry bag, AC power cord, HDMI cable, remote control, battery, quick start card Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount RoHS Compliant	Operating Conditions	5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max)				
Standard Accessories Carry bag, AC power cord, HDMI cable, remote control, battery, quick start card Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount RoHS Compliant	Uniformity	85 %				
Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount RoHS Compliant	Security	Kensington lock				
RoHS Compliant	Standard Accessories	Carry bag, AC power cord, HDMI cable, remote control, battery, quick start card				
	Optional Accessories	DLP® Link™ 3D glasses, wireless, ceiling mount				
	RoHS	Compliant				
3D Support 3D Ready - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include	3D Support					
use with 3D educational or 3D design and modelling systems.		use with 3D educational or 3D design and modelling systems.				
3D Compatibility SVGA 120Hz	3D Compatibility					
XGA 120Hz						
Speaker 6W stereo (2x3W) SRS WOW HD Audio						
On Screen Display 12 Languages: English, French, Spanish, Portuguese (Brazilian), German, Russian, Italian, Polish, Dutch, Swedish, Greek, Turkish	On Screen Display	12 Languages: English, French, Spanish, Portuguese (Brazilian), German, Russian, Italian, Polish, Dutch, Swedish, Greek, Turkish				
Optional Wireless Yes	Optional Wireless	Yes				
Features Native office viewer, media player, LED light source, optional wireless presenting	Features	Native office viewer, media player, LED light source, optional wireless presenting				

Easy To Use Remote Control

MI1500e Remote Control

- 1. Hide Button
- 2. Power Button
- 3. Up Button
- 4. Ok Button
- 5. Left Button
- 6. Down Button
- 7. HDMI Button
- 8. Media Button
- 9. Video button
- 10. LED Mode Button
- 11. Right Button
- 12. Volume Up Button
- 13. VGA Button
- 14. Volume Down Button



ML1500 Connections

- 15. SD Card Slot
- 16. USB-A
- 17. Micro USB
- **18.** VGA
- **19.** HDMI
- 20. Composite Video
- 21. Audio In
- 22. Audio Out
- 23. KensingtonTM lock
- 24. Power
- 25. USB-A

Exceptional Connectivity / Multiple Terminals



Projection distance 0.52 - 3m (16:10 Aspect ratio)						
Projection Distance (m)	Max. Horizontal Image Size (m)	Max. Vertical Image Size (m)	Max Diagonal Image Size (m)	Max Diagonal Image Size (inch)		
0.52	0.37	0.23	0.44	17.24		
1.00	0.71	0.45	0.84	33.16		
1.50	1.07	0.67	1.26	49.74		
2.00	1.43	0.89	1.68	66.32		
2.50	1.79	1.12	2.11	82.91		
3.00	2.14	1.34	2.53	99.49		

for guide purposes only

MI1500e is capable of 4:3 aspect ratio projection. When projecting a 4:3 image the image sizes, screen height and offset information will differ from the above



Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ www.optoma.co.uk

*The quoted LED Brightness rating is based on the perceived equivalent ANSI lumen brightness of a standard lamp projector. The LED brightness rating takes into account the Helmholtz-Kohlrausch (HK) effect on the perceived brightness of colours. 1Brightness will vary depending on selected projector mode, environmental conditions and usage. As is common with all projectors, brightness will decrease over the lamp lifetime. 2Typical light source achieved through testing. Will vary according to operational use and environmental conditions. 3Optoma guarantees that in normal use, Optoma DLP® colour quality will be indistinguishable from when new. Exclusions: (a) Guarantee is voided if the projector is subject to damage through misuse. (b) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is excessive (c) Guarantee will not apply if lamp brightness is below 50% due to wear or if the projector is not working due to other faults. (d) Over time worn lamps within all projector types will show a slight colour variance. Copyright © 2013, Optoma Europe Ltd. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. is a trademark of SRS Labs, Inc. WOW technology is incorporated under license from SRS Labs, Inc. Crestron®, the Crestron and RoomView® logo are registered trademarks of Crestron Electronics, Inc. Errors and omissions excepted, all specifications are subject to change without notice. DLP®, BrilliantColor™ and the DLP logo are registered trademarks of Texas Instruments. All images of products are for representation purposes only. Whilst every care is taken to provide accurate images of our products, actual products may differ slightly. Some product images may have been digitally altered by us to add an Optoma logo to the front panel. Optoma reserves the right to amend or alter actual product or product images without notice

31/10/2015 00:59