

#### **Model Name**

## **MH530 Digital Projector**

## Unique selling point

- \* 1080p resolution
- \* Easy Installation & Control
- \* Easy Maintenance





NEWED





Projection System         DLP           Native Resolution         1080p (1920 x 1080)           Brightness         3200AL           Contrast Ratio         10000:1           Display Color         1.07 Billion Colors           Lens         F=2.55-2.68, F=22-24.1mm           Aspect Ratio         Native 16:9 (5 aspect ratio selectable)           Throw Ratio         1.47-1.62 (95" ± 3% @ 3.1m)           Image Size (Clear Focus/ Maximum)         70"~150" / 300"           Zoom Ratio         1.1:1           Lamp Type         196W           Lamp(Normal/Economic/SmartEco Mode)*         4000/6000/6500 hours           Keystone Adjustment         1D, Vertical +/- 40 degrees           Projection Offset         116% ±5%
Brightness         3200AL           Contrast Ratio         10000:1           Display Color         1.07 Billion Colors           Lens         F=2.55-2.68, F=22-24.1mm           Aspect Ratio         Native 16:9 (5 aspect ratio selectable)           Throw Ratio         1.47-1.62 (95" ±3% @ 3.1m)           Image Size (Clear Focus/ Maximum)         70"−150" / 300"           Zoom Ratio         1.1:1           Lamp Type         196W           Lamp(Normal/Economic/SmartEco Mode)*         4000/6000/6500 hours           Keystone Adjustment         1D, Vertical +/- 40 degrees           Projection Offset         116% ±5%
Contrast Ratio         10000:1           Display Color         1.07 Billion Colors           Lens         F=2.55-2.68, F=22-24.1mm           Aspect Ratio         Native 16:9 (5 aspect ratio selectable)           Throw Ratio         1.47-1.62 (95" ±3% @ 3.1m)           Image Size (Clear Focus/ Maximum)         70"−150" / 300"           Zoom Ratio         1.1:1           Lamp Type         196W           Lamp(Normal/Economic/SmartEco Mode)*         4000/6000/6500 hours           Keystone Adjustment         1D, Vertical +/- 40 degrees           Projection Offset         116% ±5%
Display Color         1.07 Billion Colors           Lens         F=2.55-2.68, F=22-24.1mm           Aspect Ratio         Native 16:9 (5 aspect ratio selectable)           Throw Ratio         1.47-1.62 (95" ±3% @ 3.1m)           Image Size (Clear Focus/ Maximum)         70"−150" / 300"           Zoom Ratio         1.1:1           Lamp Type         196W           Lamp(Normal/Economic/SmartEco Mode)*         4000/6000/6500 hours           Keystone Adjustment         1D, Vertical +/- 40 degrees           Projection Offset         116% ±5%
Lens         F=2.55-2.68, f=22-24.1mm           Aspect Ratio         Native 16:9 (5 aspect ratio selectable)           Throw Ratio         1.47-1.62 (95" ±3% @ 3.1m)           Image Size (Clear Focus/ Maximum)         70"-150" / 300"           Zoom Ratio         1.1:1           Lamp Type         196W           Lamp(Normal/Economic/SmartEco Mode)*         4000/6000/6500 hours           Keystone Adjustment         1D, Vertical +/- 40 degrees           Projection Offset         116% ±5%
Aspect Ratio         Native 16:9 (5 aspect ratio selectable)           Throw Ratio         1.47-1.62 (95" ±3% @ 3.1m)           Image Size (Clear Focus/ Maximum)         70"~150" / 300"           Zoom Ratio         1.1:1           Lamp Type         196W           Lamp(Normal/Economic/SmartEco Mode)*         4000/6000/6500 hours           Keystone Adjustment         1D, Vertical +/- 40 degrees           Projection Offset         116% ±5%
Throw Ratio         1.47-1.62 (95" ±3% @ 3.1m)           Image Size (Clear Focus/ Maximum)         70"~150" / 300"           Zoom Ratio         1.1:1           Lamp Type         196W           Lamp(Normal/Economic/SmartEco Mode)*         4000/6000/6500 hours           Keystone Adjustment         1D, Vertical +/- 40 degrees           Projection Offset         116% ±5%
Image Size (Clear Focus/ Maximum)         70"-150" / 300"           Zoom Ratio         1.1:1           Lamp Type         196W           Lamp(Normal/Economic/SmartEco Mode)*         4000/6000/6500 hours           Keystone Adjustment         1D, Vertical +/- 40 degrees           Projection Offset         116% ±5%
Zoom Ratio         I.1:1           Lamp Type         196W           Lamp(Normal/Economic/SmartEco Mode)*         4000/6000/6500 hours           Keystone Adjustment         ID, Vertical +/- 40 degrees           Projection Offset         116% ±5%
Lamp Type         196W           Lamp(Normal/Economic/SmartEco Mode)*         4000/6000/6500 hours           Keystone Adjustment         1D, Vertical +/- 40 degrees           Projection Offset         116% ±5%
Lamp(Normal/Economic/SmartEco Mode)*         4000/6000/6500 hours           Keystone Adjustment         ID, Vertical +/- 40 degrees           Projection Offset         I16% ±5%
Keystone Adjustment         ID, Vertical +/- 40 degrees           Projection Offset         I16% ±5%
Projection Offset 116% ±5%
Resolution Support VGA(640 x 480) to WUXGA_RB(1920 x 1200) * RB= Reduced blanking
Horizontal Frequency 15k~102KHz
Vertical Scan Rate 23 ~ 120 Hz
Compatibility         HDTV Compatibility         480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility NTSC, PAL, SECAM
3D Compatibility  PC: 120Hz Frame Sequential 3D for resolutions up to WXGA, PC: 60Hz Top 3D for resolutions up to SXGA+
Interface Computer in (D-sub 15pin) x 2 (Share with component)
Monitor out (D-sub 15pin) x I (Only support Computer I)
Composite Video in (RCA) x I
S-Video in (Mini DIN 4pin) x I
UDM(4.4)
HDMI (1.4a) x l
Audio in (Mini Jack) x I
Audio in (Mini Jack) x I
Audio in (Mini Jack) x I  Audio out (Mini Jack) x I
Audio in (Mini Jack) x I  Audio out (Mini Jack) x I  Speaker 2W x I
Audio in (Mini Jack) x I  Audio out (Mini Jack) x I  Speaker 2W x I  USB (Type B) x I (Download & page/down)
Audio in (Mini Jack) x    Audio out (Mini Jack) x    Speaker 2W x    USB (Type B) x   (Download & page/down)  RS232 (DB-9pin) x
Audio in (Mini Jack) x    Audio out (Mini Jack) x    Speaker 2W x    USB (Type B) x   (Download & page/down)  RS232 (DB-9pin) x    IR Receiver x   (Front)
Audio in (Mini Jack) x I  Audio out (Mini Jack) x I  Speaker 2W x I  USB (Type B) x I (Download & page/down)  RS232 (DB-9pin) x I  IR Receiver x I (Front)  Dimensions  Dimensions(W x H x D) 283x95x222 mm
Audio in (Mini Jack) x   Audio out (Mini Jack) x   Speaker 2W x   USB (Type B) x   (Download & page/down) RS232 (DB-9pin) x   IR Receiver x   (Front)  Dimensions Dimensions(W x H x D) 283x95x222 mm Weight 1.96KG
Audio in (Mini Jack) x   Audio out (Mini Jack) x   Speaker 2W x   USB (Type B) x   (Download & page/down) R5232 (DB-9pin) x   IR Receiver x   (Front)  Dimensions Dimensions(W x H x D) 283x95x222 mm Weight 1.96KG  Power Power Supply AC100 to 240 V, 50 to 60 Hz

On-Screen	Display	Languages

Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/

Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)

Dynamic / Presentation / sRGB / Cinema / (3D) / User 1 / User 2 Picture Modes


Accessories Standard Optional Remote Control w/ Battery P/N: 5J.J4R05.001 Spare Lamp Kit Power Cord (by region) Ceilling Mount P/N: 5J.J2K01.001 User Manual CD P/N: 5J.J0T14.011 3D Glasses Quick Start Guide Carry bag Warranty Card (by region) VGA(D-sub 15pin) Cable

Lamp in this product contains mercury. **Environmental Notice** 

To dispose of the product or used lamps, consult your local environment authorities for regulations or see www.lamprecycle.org. \*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.


<sup>\*\*</sup> Default mode is **Presentation**. When 3D is on, Picture Modes only shows 3D. When 3D is off, it is not shown in Picture Modes.


## **Distance Chart**




Screen size			Projec	tion distanc	e (mm)		
Diagonal		w		Min distance		Max distance	
Inch	mm	(mm)	(mm) H	H (mm)	(max. zoom)	Average	(min. zoom)
40	1016	886	498	1302	1368	1435	
50	1270	1107	623	1627	1710	1793	
60	1524	1328	747	1953	2052	2152	
70	1778	1550	872	2278	2394	2510	
80	2032	1771	996	2603	2736	2869	
90	2286	1992	1121	2929	3078	3228	
100	2540	2214	1245	3254	3420	3586	
110	2794	2435	1370	3580	3762	3945	
120	3048	2657	1494	3905	4104	4304	
130	3302	2878	1619	4231	4446	4662	
140	3556	3099	1743	4556	4788	5021	
150	3810	3321	1868	4881	5130	5380	
160	4064	3542	1992	5207	5473	5738	
170	4318	3763	2117	5532	5815	6097	
180	4572	3985	2241	5858	6157	6455	
190	4826	4206	2366	6183	6499	6814	
200	5080	4428	2491	6509	6841	7173	
250	6350	5535	3113	8136	8551	8966	
300	7620	6641	3736	9763	10261	10759	

# Wall mount/Ceiling mount Chart







Unit: mm

## Dimension



