



ULTRA SHORT THROW PROJECTORS

LV-WX300USTi LV-WX300UST

Recommended for:


- K-12 Education
- Higher Education
- Corporate
- Small Businesses
- Retail



ULTRA SHORT THROW FOR MAXIMUM FLEXIBILITY

Canon's new LV-WX300USTi and LV-WX300UST Projectors give users the power to present large images in tight spaces. The Ultra Short Throw capabilities of both models allow the projection of 80" diagonal images only 11" from the projector, and the LV-WX300USTi's interactive software allows for a collaborative experience – making this a powerful tool that will help engage audiences.

WORK AND STUDY WITH INTERACTIVE, ULTRA SHORT THROW PROJECTION



Up to four Interactive Pens, or other objects (fingers), can write simultaneously for collaborative experience



Finger Touch writing
(Requires optional Finger Touch Module)

- Ideal for use in space-restricted environments like smaller classrooms and offices
- Interactive functions allow users to greatly enhance presentation and lecture experiences by encouraging audience involvement
- Screens can be captured (as PDF* or JPEG files) and video can be recorded for sharing to reinforce key content/concepts

*Feature only available with Windows version.

KEY FEATURES

- Ultra Short Throw with 0.35:1 Throw Ratio
- Project 100" Diagonal Image only 18-inches from Projector
- WXGA (1280 x 800)
- 3000 Lumens
- Up to 7500:1 Contrast Ratio
- DLP Technology with BrilliantColor™ System
- Interactive Projection with Bundled Software (LV-WX300USTi Only)
- Dual HDMI Inputs
- Compact Design for Versatile Installation Options
- Power Saver Mode Extends Lamp Life to 8000 Hours, while also Reducing Power Consumption and Fan Noise

DLP BrilliantColor™

SPECIFICATIONS

PROJECTION SYSTEM	
Imaging Device	0.65" DMD x1
Aspect Ratio	16:10
Native Resolution	1280 x 800 (WXGA)
Brightness ²	3000 Lumens (Full Power) / 2500 Lumens (Power Saver)
Contrast ⁵	7500:1
Image Size	80 - 100"
Digital Keystone	V±40°
F Number, Focal Length	F2.5, 5.1mm
Uniformity	80%
Zoom Ratio	Fixed
Throw Ratio ¹	0.35:1
Digital Zoom	2x Maximum
Focus	Manual
Lens Shift	75%, Fixed


IMAGE ADJUSTMENTS	
Image Mode	Standard / Presentation / Dynamic / Photo / sRGB / User
Color Adjustment	Color Level, Color Balance, Color Temperature, Gain (R,G,B), Offset (R,G,B)
Wall Color Correction	Normal / Greenboard / Adjust (custom)
Mounting	Ceiling / Wall / Table
Tilt Angle	Front: 1, Rear: 2 (Max angle: 2° elevation)

INPUT SIGNALS	
Scanning Frequency	H: 23.97 - 120 Hz, V: 15.625 - 101.6 kHz
Analog PC Input	UXGA / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA / MAC
Digital PC Input	UXGA / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA
Digital Video Input	1080p / 1080i / 720p / 576p / 480p
Component Video Input	1080p / 1080i / 720p / 576p / 576i / 480p / 480i
Video Input / S-Video Input	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N / PAL - 60
Dot Clock	165 MHz (Maximum)

REMOTE CONTROL	
Remotes	Wireless Infrared (supplied) or Wireless with Laser Pointer (optional)

DIMENSIONS

Images shown are of the LV-WX300USTi



WHAT'S IN THE BOX

- Projector
- Power Cord
- Computer Cable (Mini Dsub15-Mini Dsub15)
- Projector Remote Control LV-RC10 (includes battery)
- Quick Start Guide (Book)
- User's Manual (CD-ROM)
- Warranty Card
- USB Cable^{**} (Type-A to Mini Type-B)
- Interactive Pens LV-IP01^{***} (includes two pens with batteries)

¹ Calculated value for 87" image ² Lamp mode is Full Power/Power Saver. Brightness in Power Saver mode is only a calculated value, and is not guaranteed as specified ³ Low power mode is Off/On

⁴ Applies to LV-WX300USTi only ⁵ Image Mode: Presentation, Lamp Mode: Full Power

⁶ New accessory/product ^{**} Applies to LV-WX300USTi only ^{***} When installing this wall mount, please follow all safety guidelines in its accompanying Instruction Manual.

©2015 Canon U.S.A., Inc. All rights reserved. Not responsible for typographical errors. Specifications subject to change without notice. Products not shown to scale. Certain images and effects are simulated. Canon is a registered trademark of Canon Inc. in the United States and may also be a trademark or registered trademark in other countries. All other products and brand names may be registered trademarks, trademarks or service marks of their respective owners in the United States and/or other countries.

TERMINALS	
Mini Dsub15 x2	Analog PC / Component Video Input
HDMI x2	Digital PC / Digital Video Input
Mini DIN4	S-Video Input
RCA	Video Input
2RCA	Audio Input
Mini Jack x2	Audio Input, Audio Output
Mini Jack	Mic Input
Mini Dsub15	Analog PC Output
RJ-45	Network Connection (100BASE-TX, 10BASE-T)
USB Type B	For Mouse Control / Firmware Update
USB Mini B ⁴	For Interactive Function
USB Type A ⁴	For Finger Touch Module LV-FM01 (optional)


BUILT-IN SOUND	
Internal Speaker	10W x2, Stereo

LAMP	
Type	Super-high Pressure Mercury Lamp
Life	5000 Hours (Full Power) / 8000 Hours (Power Saver)
Power ²	230 / 200 W

RATINGS	
Fan Noise ²	33dB (Full Power) / 29dB (Power Saver)
Power Consumption ²	300 / 240 W
Standby Power ³	6.0 / 0.5 W
Power Voltage	AC 100 - 240V, 50 / 60 Hz
Operating Temperature	41°F - 104°F (5°C - 40°C)
Storage Temperature	-4°F - 140°F (-20°C - 60°C)
Dimensions (W x H x D)	LV-WX300USTi: 11.3" x 7.6" x 14.7" / 287.5 mm x 193.6 mm x 374.5 mm (including protrusion) LV-WX300UST: 11.3" x 6.6" x 14.7" / 287.5 mm x 167.6 mm x 374.5 mm (including protrusion)
Weight	11 lbs. (5.0 kg)
Projector Warranty	3 Years (parts and labor)
Lamp Warranty	120 Days

CONNECTABILITY

Image shown is of the LV-WX300USTi



ACCESSORIES

- Projector Remote Control with Laser Pointer (Wireless) LV-RC09^{*}
- Projector Remote Control LV-RC10^{*} (includes battery)
- Wall Mount LV-WL02^{**}
- Finger Touch Module LV-FM01^{**}
- Interactive Pen LV-IP01^{**}
- Replacement Lamp LV-LP41^{**}

