



CASIO® Laser & LED Hybrid Light Source

XJ-UT310WN

ULTRA SHORT THROW SERIES

CASIO Ultra Short Throw series projectors projects bright, crisp, images at close range with a full assortment of connectivity & features

LampFree® Projector



XJ-UT310WN



LampFree Benefits:

- 3100 Lumens
- Ultra Short Throw Ratio (0.28:1)
- RJ-45 Wired LAN
- Auto Brightness Adjustment
- Built-in 16w Speaker
- DLP Technology
- DLP 3D Ready
- Closed Captioning
- Expanded input/output connectivity — 2 RGB input, 1 RGB output, video, HDMI, RS-232C, audio in/out, mic in 1 USB A/B, 1 USB Display and 1 RJ-45 Wired LAN

USB:

- Wireless presentations from PC or Mac
- Built-in memory: 2GB
- Logo Capture – start up screen
- Presentations from your thumb drive
- USB display: send video to the projector from almost any device via an inexpensive USB cable

LampFree Features:


- Laser & LED Hybrid Light Source
- Mercury Free
- Quick Start (8 seconds to full brightness)
- Instant Off – no cool down required
- 20,000 Hour Operating Life
- No Lamp Replacement
- No Down Time
- Low Power Consumption
- Intelligent Brightness Control

Low Carbon Footprint:

Eco Mode can save as much as 50%, and we link it to an ambient light sensor, producing great images by automatically adjusting the projector brightness to the brightness of the room.

Warranty Information:

3 year warranty on the projector and 3 years (or 6,000-hour usage) on the light source. Education market -3 year warranty on the projector or 5 years (10,000 hour usage) on the light source.



* Extended Use Applications are defined as operation of 10 hours per day for 5 or more days per week. Under these conditions the light source warranty is one (1) year or 6000 hours.

© 2014 Casio America, Inc. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. in the United States and/or other countries. Specifications were thought to be correct at time of publication. All specifications and features are subject to change without notice. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XGA and WXGA are registered trademarks of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademark of HDMI Licensing, LLC. MobiShow is a registered trademark of Awind Inc. iPhone, iPad and iPod are registered trademarks of Apple Inc. Android is a trademark of Google Inc. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners.

CASIO Projector Specifications

Ultra Short Throw Series XJ-UT310WN	
	WXGA
Native Resolution	1280x800
Native Aspect Ratio	16:10
Brightness	3100 lumens
Display Device	0.65-inch DLP® chip
Contrast Ratio	1800:1
Lens Type	Fixed/Manual Focus
Lens Specs F/f	F2.3/f4.2mm
Lens Offset	68%
Light Source	Casio Laser & LED Hybrid (Up to 20,000 Hours)
Screen Size (Min-Max)	50 to 110-inch diagonal
Projection Range	
60-inch screen	18.8" (77" W screen)
100-inch screen	21.5" (87" W screen)
Minimum Throw Distance	11.5" (50" W diagonal)
Throw Ratio	0.28:1
Keystone Correction	Vertical + or - 5°(Manual)
Color Reproduction	Full color (16.77 million colors)
Power Source	AC 100~240V, 50/60Hz
Power Consumption	230 watts- Eco Mode "off" Bright selected / 110 watts Eco Mode "Eco 5" Selected
Standby	0.12 w (LAN OFF), 2.3 w (LAN ON)
TERMINAL CONNECTIVITY	
Video Signal Compatibility	
Video Systems	NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM
DTV/HDTV	480i/480P/576i/576P/720P/1080i/1080p
Maximum Computer Input	UXGA (1600 x 1200)
INPUTS	
RGB/Component Video Input	mini D-Sub 15 pin x 1 (Also use as YCbCr/YpPr input— commercially available adapter required)
HDMI	HDMI Type A x 1 (480p~1080p)
USB Display	Yes
Composite Video	Composite Video (RCA) x 1, S-Video x 1
Audio	RCA (R/L) x1, Stereo mini x 2
Built-in Memory	2GB (PDF, JPEG, BMP, PNG, GIF, AVI, MOV, MP4)
USB	Type A (USB2.0) x1 / Type B(USB2.0) x1
Logo Transfer	Micro B(USB1.1) x1
Wireless Capability IEEE802.11 b/g/n compatible	Wireless LAN Adapter (YW-40) included
OUTPUTS	
Audio	Stereo Mini x 1, Mini D-sub 15 pin x 1
Microphone (dynamic compatible)	3.5 mm Minijack
AUDIO AND CONTROL SYSTEMS	
Audio system	16W x1 Monaural Speaker
Control Terminal	
RS-232	RS-232C (D sub 9 pin) x 1 Cross Cable (Null Modem) required)
LAN	RJ-45 x 1
Control System Compatibility	AMX, Crestron, Extron, SP Controls, PJLink
OTHER INFORMATION	
Usage Environment	
Operating Temp/Humidity	41~95°F / 20~80% (non condensation)
High Altitude Mode	Yes (for operation 5,000~10,000 ft)
Extended operation (24 x 7)	Yes — Note: Projector must be turned off once every 24 hours
Rotation Projection	No
Remote Control Range	16.4 ft Maximum
Security Compatibility	Kensington™ Compatible / Power On Password
Ceiling Mountable	Yes (YM-80 Optional)
Ceiling Mount Screws	(Type x Qty) M4 x 4, not included (Insert depth 5-8 mm)
Limited Warranty	3 years Parts and Labor plus 3 years or 6,000 hours light source, see Warranty Statement included with product for complete details.
Included Accessories	Wireless remote control, YW-40 Wireless adapter, 6' RGB cable, 6' AC Power Cord, Cable Cover and Setup Manual (Printed)
Included Software	Network Connection (Windows® and Mac) EZ-Converter FA (Windows®)
Optional Accessories	Wall Mount (YM-80) Active Shutter 3D Glasses (YA-G30) 2D-3D Conversion Software (YA-D30)
Cabinet Color	White / Gray Trim
Dimension (W x D x H)	
Including Projections	16.5 x 13.1 x 6.0 in
Excluding Projections	16.5 x 13.1 x 5.6 in
Weight	12.1 lbs
Packing Information	
Carton Dimensions	23.4"L x 18.5"W x 10.8"H
Carton Weight	21.2 lbs.
UPC Code	079767468101
Manufactured in	Japan