

# CP-EX303

## Our New Portable 3LCD Projector



**Introducing our innovative portable 3LCD CP-EX303 projector which combines all our technical expertise with our market leading knowledge.**

This new, portable projector can produce 3,300 ANSI, has a 20,000:1 contrast ratio and a resolution of 1024 x 768.

So whether you are on the move or in an office, our CP-EX303 portable projector is the perfect solution for today's mobile professionals. It combines simple usability with powerful performance in a lightweight and compact design, enabling users to set it up and get working in seconds.

### Key Features:

XGA 1024 x 768 resolution

3,300 ANSI lumens white/colour output

20,000:1 Contrast Ratio

Images up to 300" diagonal

Easy to use and simple to set-up

Light weight – only 3.5kg

# CP-EX303 3LCD Portable Projector

## Technical Specifications

<b>Display System</b>	3 LCD 16mm (0.63")	<b>Digital Input</b>	HDMI x 1 (HDCP compliant)
<b>Panel Structure</b>	3LCD	<b>Analogue Input</b>	15-pin Mini-D-Sub x 2, RCA Jack x 1
<b>Resolution</b>	XGA (1024 x 768)	<b>Video Output</b>	15 pin Mini D-Sub x 1 (shared with analog computer input)
<b>Light Output (Brightness) ANSI Lumens (Normal)</b>	3,300 (Normal)	<b>Audio Input</b>	RCA Jack (L/R) x 1
<b>Contrast Ratio</b>	20,000:1	<b>Audio Output</b>	3.5mm Stereo Mini Jack x 1
<b>Lamp Life (Hours)</b>	6000 (Normal) / 12500 (Eco)	<b>RS-232C Control</b>	1 x 9-pin D-Sub
<b>Lens</b>	Built-in	<b>Wireless LAN</b>	No
<b>Lens Zoom</b>	Manual zoom x 1.2	<b>Wired LAN</b>	No
<b>Lens Focus</b>	Manual focus	<b>USB Type-A</b>	No
<b>Projection Lens F Number</b>	2.1-2.3	<b>USB Type B</b>	No
<b>Focus Distance</b>	0.9 – 9.1m (Wide) / 1.1 – 10.9m (Tele)	<b>Power Supply</b>	AC 100V – 120V / AC 220V – 240V (50/60Hz)
<b>Distance to Width Ratio/ Throw Ratio (:1)</b>	1.5 - 1.8	<b>Operating Power Consumption</b>	280W
<b>Diagonal Display Size</b>	30 - 300"	<b>Standby Power Consumption</b>	Less than 0.35W
<b>Installation</b>	Ceiling, Tabletop, Rear	<b>Weight</b>	3.5kg
<b>Speakers</b>	1W mono	<b>Dimensions (W x H x D)</b>	349 x 264 x 88 mm
<b>Digital Keystone Correction (Degrees)</b>	Vertical ± 30°	<b>Noise (Normal)</b>	37dB (Normal) / 29dB (Whisper)
<b>Picture Modes</b>	Normal, Cinema, Dynamic, Board (Black), Board (Green), Whiteboard, Daytime, Photo, DICOM SIM	<b>Filter Life (Hours)</b>	5,000
<b>Picture Adjustments</b>	ASPECT selection (Normal/4:3/16:9/16:10/14:9/Zoom), Perfect Fit (4 corners and 4 sides), Frame Lock (Data signal with vertical frequency of 49 to 51Hz, 59 to 61Hz), HDCR, Image blank by RS232C/Remote control, Image Optimizer, Magnify, Mirror Reverse Image, Up-side Down Image	<b>Certification</b>	CE Marking, EN61000-3-2, EN61000-3-3, EN55032(class A), EN55024(EMC directive), EN60950-1 (Low voltage directive), WEEE/RoHS compliant
<b>Operating Features</b>	Audio pass through, Audio ports assign, Audio out (standby) and monitor out / selectable source with MENU, Auto eco mode, Auto power off, Auto signal search, Direct power on, Image blank by RS232C/Remote control, LED lamps (power, lamp, temp), Magnify 4 times (XGA) by RS232C / remote control, MyButton by remote control, MyMemory, MySource, MyText, MyScreen, Picture freeze by RS-232C / remote control, Serial number displayed on EASY MENU and on the side of projector, Source naming (in English), Stand-by audio	<b>Computer</b>	IBM Compatible VGA, SVGA, XGA, WXGA/WXGA+/SXGA/SXGA+/UXGA (compressed), MAC16"
<b>Security Features</b>	PIN Security Lock, MyScreen Password Lock, Transition Detector, MyText Password Lock, Key Lock (Key pad, Remote Control)	<b>Video</b>	525i (480i), 525p (480p), 625i (576i), 1125i (1080i@50/60), 750p (720p@50/60), 1125p (1080p@50/60)
<b>Supported Languages</b>	34 Languages (English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkey, Arabian, Persian, Czech, Danish, Hungarian, Romanian, Slovenian, Croatian, Greek, Lithuanian, Estonian, Latvian, Thai, Portuguese (Brazil), Indonesian, Vietnamese, Hebrew)	<b>Supplied Accessories</b>	Power Cable (1.8m), Computer Cable (2m), Remote Control Unit x1, Concise User Manual x1, Security Label x1, Adapter Cover x1, Hook Metal x1, Screw x1, HDMI Cable Holder (x2), Cable Tie (large x1, medium x2, small x1), AA Batteries x2
		<b>Remote Control</b>	HLC03031
		<b>Replacement Lamp, Filter</b>	DT02081 (without Filter) / UX39561
		<b>Projector/ Light source Warranty</b>	3 years / 6 months (for education and extended warranties please contact your local dealer)



Dealer Stamp

**HITACHI**  
Inspire the Next

Hitachi Digital Media

Hitachi Europe Ltd, Whitebrook Park, Lower Cookham Road,  
Maidenhead, Berkshire SL6 8YA, United Kingdom

Tel: +44 (0)1628 585 000 / Fax: +44 (0)1628 585 163

www.hitachidigitalmedia.com