

NEC V260

Order Code: 60003176

NEC V260 Value Projector

Get the Ultimate 3D Experience with a 3D ready DLP®Projector from NEC. DLP®-Link™ technology allows 3D images to be projected with the aid of a single projector and active glasses without special screens, filters or emitters. The impression of 3D is created by the interaction with the active LCD shutter glasses. The easy to set up alternative to traditional 3D stereo projection.

An ideal solution for classrooms, (small) meeting rooms, cross-use (private/professional), mobile / cooperative applications.



DELIVERING GENUINE BENEFITS

Carbon Savings Meter - to encourage the use of EcoMode.

Control and Monitoring - via RS-232.

Green EcoMode Button - on remote.

Higher Efficiency, Lower Power Consumption - full ErP compliance.

Long Lamp Life - up to 5000 hrs.

Virtual Remote - for direct PC control.

3D ready - future-proof DLP®-Link™ technology with 120Hz and Top/Bottom, 60Hz.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.



OUTSTANDING PERFORMANCE

- **3D Ready DLP®-link™** technology with 120Hz and Top/Bottom, 60Hz
- **Excellent and Brilliant Colours** - due to VIDi technology
- **Contrast 2000:1**
- **Quick Start** - Direct Power Off
- **7W Speaker**
- **Carbon Meter** - indicating the reduced amount of CO₂ emissions by the use of ECO mode



SPECIAL CHARACTERISTICS

3D ready DLP®-Link™, 120Hz and Top/Bottom, 60Hz, 6-segment Colour Wheel, Auto Power Start, BrilliantColor™ and VIDi technology, Carbon Savings Meter, Long Life Lamp, Manual vertical Keystone Correction (V= ±40°), NaViSet Administrator 2, Plug & Play, Quick-Start-/Direct-Power-Off Function, Virtual Remote for direct PC control, 100% recyclable packaging, Downloadable manuals, RoHs compliant, ErP compliant, Intelligent Power Management, WEEE



Energy Efficiency Intelligent Power Management

Ecological Materials 100% recyclable packaging; Downloadable manuals

Ecological Standards RoHs compliant; ErP compliant; WEEE

Technical Specification NEC V260

| | |
|--------------------------------------|---|
| IMAGE | |
| Display | 1 x 1.4 cm (0.55") DDR DMD Chip (Aspect Ratio 4:3) |
| Native Resolution | 800 x 600 (SVGA) |
| Contrast Ratio ¹ | 2000:1 |
| Brightness ¹ | 2600 ANSI Lumen |
| Lamp | 180 W AC |
| Lamp Life [hrs] | 3500 (5000 Eco Mode) |
| Projection Factor | 1.95 – 2.15 : 1 |
| Projection Distance [m] | 1.2 – 13 |
| Screen Size (diagonal) [cm] / [inch] | Minimum: 76; Maximum: 762 |
| Zoom | Manual |
| Focus Adjustment | Manual |
| Supported Resolutions | 1920 x 1080; 1600 x 1200; 1400 x 1050; 1280 x 1024; 1280 x 960; 1280 x 720; 1024 x 768; 832 x 624; 800 x 600; 640 x 480 |
| Frequency | Horizontal: 15 – 100 kHz; Vertical: 50 – 120 Hz |
| CONNECTIVITY | |
| RGB (analog) | Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin |
| Video | Input: 1 x RCA |
| S-Video | Input: 1 x Mini DIN 4-pin |
| Audio | Input: 1 x 3.5 mm Stereo Mini Jack |
| PC Control | Input: 1 x D-Sub 9 pin (RS-232) (male) |
| Video Signals | PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-N; PAL-M |
| REMOTE CONTROL | |
| Remote Control | Aspect Ratio; Audio Control; Auto Adjust; Automatic Picture Adjustment; Freeze-function; Help-function; ID set; Keystone Correction; Lamp Mode Control; Magnify-function; Picture Adjust; Picture Mode; Picture Mute; Source Select |
| ELECTRICAL | |
| Power Supply | 100-240 V AC; 50 - 60 Hz |
| Power Consumption [W] | 233 max.; 210 Eco Mode; 4 Network Stand-By Mode; 0.8 Power Savings Mode |
| MECHANICAL | |
| Dimensions (W x H x D) [mm] | 310 x 95 x 247 (without lens and feet) |
| Weight [kg] | 2.5 |
| Fan Noise [dB (A)] | 31 / 34 (Eco / Normal) |
| ERGONOMICS | |
| Safety and Ergonomics | CE; ErP; TÜV GS; RoHS |
| Speakers [W] | 1 x 7 (mono) |
| WARRANTY | |
| Projectors | 3 years pan-European service |
| Lamp | 6 months, max. 1000 hrs |
| SHIPPING CONTENT | |
| Shipping Contents | Projector; IR Remote Control (RD-443E); Mini D-SUB Signal Cable (1.8 m); Power Cord; Users Manual on CD-ROM; Quick Setup Guide; Lens Cap |
| OPTIONAL ACCESSORIES | |
| Optional Accessories | 3D Starter Kit (NP01SK3D); DLP-Link 3D Glasses (NP01GL); Lamp (NP13LP); Universal Ceiling Mounts (NP01/02/03/04/05UCM) |

¹ Compliance with ISO21118-2005