

NEC L51W LED

Order Code: 60003377

NEC L51W LED Professional Mobile Projector

Get innovative LED technology in an extremely compact and lightweight format and with a very stylish look. The L51W LED is a fully featured mobile projector with a comprehensive input panel as well as an integrated office viewer for PC-less and wireless presentations. Low power consumption and a lifetime of the light source of 20.000 hrs result in a very low total cost of ownership.

An ideal solution for mobile and corporate applications as well as cross-use (private/professional).

DELIVERING GENUINE BENEFITS

Ease of Use - thanks to auto keystone and auto input detection.

Extremely Compact and Lightweight - due to innovative LED technology.

Reduced to the Max - minimalistic design with full connectivity and integrated power supply.

Wide format - for extra space in presentations and video content in native aspect ratio - no quality loss due to format scaling.

Wireless presentation - run presentations and slide shows wireless from your smart phone, tablet or PC.





OUTSTANDING PERFORMANCE

- **Optional WLAN** For wireless presentation
- **3D Ready** DLP®-link[™] technology with 120Hz
- Fast and Reliable LED Technology
- HDMI & USB Input to connect various digital devices
- USB and SD Card Reader for PC-less presentations and slide shows
- Full Office Viewer supporting office file formats, images and video

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 28.06.2012

NEC L51W LED



SPECIAL CHARACTERISTICS

1 GB integrated memory, 3D ready, Auto Power ON/OFF, Auto Power Start, Automatic and manual vertical Keystone Correction (V= $\pm 40^{\circ}$), Digital Zoom, Kensington security slot, Keypad Lock, LED Light Source, Lens Cover, Off-Timer, Optional WLAN, Quick-Start-/Direct-Power-Off Function, SD Card Reader, Tripod thread, USB Display, USB Viewer, Wall Colour Correction



Energy Efficiency	Off-Timer; LED light source with 20.000 hrs life time; Very low power usage
Ecological Materials	100% recyclable packaging; Downloadable manuals

Ecological Standards RoHs compliant; ErP compliant; WEEE

MAGE	
Native Resolution	1280 x 800 (WXGA)
Brightness 1	500 ANSI Lumen
Contrast Ratio 1	4000:1
Lamp	LED Light Source (no lamp required)
Lens	F= 1.5, f= 13.92 mm
Projection Factor	1.4 : 1
Projection Angle [°]	13.8
Projection Distance [m]	0.52 - 3
Screen Size (diagonal) [cm]	Minimum: 43.2 / 17"; Maximum: 254 / 100"
Focus Adjustment	Manual
Supported Resolutions	1920 x 1080 (HDTV / 1086 i); 1680 x 1050 (WSXGA+); 1440 x 900 (WXGA); 1400 x 1050 (SXGA+); 1366 x 768 (WSXGA+); 1280 x 10 (SXGA); 1280 x 960 (QVGA); 1280 x 800 (WXGA); 1280 x 768 (WXGA); 1280 x 720 (720 p); 1152 x 870 (MAC); 1152 x 864 (SXG 1024 x 768 (XGA); 800 x 600 (SVGA); 720 x 576 (576 i/p); 720 x 4 (480 i/p); 640 x 480 (VGA)
Frequency	Horizontal: 30 – 100 kHz; Vertical: 50 – 85 Hz
CONNECTIVITY	
RGB (analog)	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr)
HDMI®	Input: 1 x HDMI® (Deep Color, Lip sync)
Video	Input: 1 x RCA
Audio	Input: 1 x 3.5 mm Stereo Mini Jack
USB	1 x Type A (USB 2.0 high speed); 1 x Type B
Video Signals	PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-N; PAL-M
SD Card	yes
REMOTE CONTROL	
Remote Control	Audio Control; Auto Adjust; Digital Zoom; Source Select
LECTRICAL	
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	105 Normal Mode; 70 Eco Mode; 0.5 Power Savings Mode
/IECHANICAL	3
Dimensions (W x H x D) [mm]	226 x 43 x 174 (without lens and feet)
Weight [kg]	1.2
Fan Noise [dB (A)]	32 / 38 (Eco / Normal)
OPTIONAL ACCESSORIES Optional Accessories	Wireless LAN module NP03LM (Europe, South Africa), NP02LM2 (Middle East, Africa, Ukraine), NP02LM3 (Russia)
RGONOMICS	
Safety and Ergonomics	CE; ErP; TÜV GS; RoHS
Speakers [W]	1 x 2 (mono)
VARRANTY	
Projectors	3 years pan-European service
-	
SHIPPING CONTENT Shipping Contents	Projector; IR remote control; Mini D-SUB Signal Cable; Power Corr Soft Case; Users Manual on CD-ROM; Quick Setup Guide

¹ Compliance with ISO21118-2005

