SONY

make.believe

Data Projector VPL-DX120

Key Features


- 2,600 lumens (ISO 21118)
- Native XGA (1,024x768) resolution
- High contrast ratio
- BrightEra® Panel
- Long-lasting lamp

Recommended lamp replacement time 7000h (low mode)


- Energy efficient design
- Auto power saving mode
- Blank with lamp dimming
- 4 lamp mode (High, Std, Low, Auto*) *Auto lamp control by picture brightness
- ECO MODE key
- Convenient terminals including HDMI
- 1W Speaker
- Auto Keystone Correction
- Off and Go Function
- Carry Case

Dimensions (Front)

Unit: mm (inches)



Dimensions (Bottom)




XGA / 2,600 lm

Optical		
2600 lumens (Lamp mode: High)		
Light Output / Color Light Output		1900 lumens (Lamp mode: Standard)
		· · · · ·
		1700 lumens (Lamp mode: Low)
LCD Panels		0.63"x3 BrightEra LCD Panel
Panel Display Resolution		XGA (1024x768 dots)
Contrast Ratio		2,500:1 (Full white/full black)*1
Light Source		Ultra high-pressure mercury lamp 210 W type
Recommended Lamp		3000H (Lamp mode: High)
Replacement Time*2		5000H (Lamp mode: Standard)
·		7000H (Lamp mode: Low)
Filter Cleaning Cycle*2		Max. 1000H
Projection Lens	Zoom / Focus	Approx. 1.2x Manual Zoom / Manual Focus
	Throw Ratio	1.47:1 to 1.77:1
Screen Size		30" to 300"
Interface		
Computer and Video Input/Output		Mini D-sub 15-pin (RGB/Y Pb Pr)
	INPUT A	Audio: Stereo mini jack
		HDMI (Digital RGB/Y Pb Pr, Digital Audio)
	INPUT B	(HDCP support)
	VIDEO IN	Pin Jack
		Audio : shared with INPUT A
General		
Speaker		1W (mono)
Scanning Frequency		H: 15 to 92 kHz, V: 48 to 92 Hz
- Courring Freque	Computer	Maximum display resolution :
Display Resolution	Signal Input	UXGA 1600x1200 dots
	Signai input	Video (Composite), 15k (480/60i, 575/50i),
	Video Signal Input	DTV (480/60p, 575/50p, 720/60p, 720/50p,
		1080/60i, 1080/50i, 1080/60P, 1080/50P)
		NTSC3.58, PAL, SECAM, NTSC4.43, PAL-M,
Color System		PAL-N
LIDC Co. do		
UPC Code		0 27242 85429 1
Power Requirements		AC 100 V to 240 V, 2.9 A to 1.2 A, 50 Hz/60 Hz
Power Consumption		282 W (AC 100 V-120 V)
		270 W (AC 220 V-240 V)
Standby Mode		<0.5 W (Low) (AC 100V-120 V)
Power Consumption		<0.5 W (Low) (AC 220V-240 V)
Dimensions (WxHxD)		315 x 75 x 230.5 mm
(without protrusion)		12 13/32 x2 15/16 x9 1/16 "
Mass		2.5 kg /5 lb 7 oz
Optional Accessories		
Replacement Lamp		LMP-D213
Service Parts		
Replacement Filter		4-437-398-01 (FILTER)
		(Filters are cleanable)
Replacement Remote		1-490-463-11 (RM-PJ8)

^{*1} The value is average with lamp dimming.

Connector Panels



For more information, visit: www.sony.com/projectors

^{*2} Expected maintenance time not guaranteed. Lamp and filter performance will vary based on operating environment and use.