

Key **Features**

Extended Lifespan | Automatic Sleep Timer | Auto Power Off | Bright Images in Any Environment | Amazing Colour Accuracy



Product **Description**

The ViewSonic PA503S offers impressive visual performance in small business meeting rooms and classrooms. With higher brightness and longer lamp life, PA503S projector is guaranteed to reproduce the finest of details in any environment for much longer. ViewSonic exclusive SuperColour™ technology offers a wider range of displayable colour ensuring true-to-life colour accuracy in both bright and dark environments without sacrificing image quality.



- 1. Keypad
- 2. LED indicator
- 3. Lamp cover
- 4. Security lock
- 5. Zoom/Focus
- 6. Front IR
- 7. Projection Lens
- 8. Audio in/out
- 9. HDMI
- 10. Dual VGA
- 12. Mini USB
- 11. VGA out
- 13. Video
- 14. Kensington® Lock Slot 15. RS232

Visit Us — www.viewsonic.com

19.02.2019, 14:03 1 or 2

100-240V+/- 10%,

Spanish, Thai,

SPECIFICATION OTHERS

Projection system: 0.55" SVGA Power Supply Voltage:

50/60Hz AC Native Resolution: 800x600

Normal: 260W Power Consumption: DC3 DC type: Standby: <0.5W

3600 ANSI Lumens Brightness: 0~40°C Operating Temperature: Contrast Ratio with SuperEco Carton: Brown 22000:1

mode: Net Weight: 2.2kg Display Colour: 1.07 Billion Colours

Dimensions (WxDxH) 294x218x110mm Light Source: Lamp w/adjustment foot:

Light source life (Nor/SuperEco): 5000/15000 English, French,

Lamp Watt: 190W Korean, German, Italian, Russian, F=2.56-2.68, Swedish, Dutch, Lens: f=22-24.1 mm Polish, Czech,

Language: T-Chinese, Projection Offset: 120%+/-5% S-Chinese, Japanese, Turkish, Portuguese, Finnish, Throw Ratio: 1.96~2.15 Indonesian, India,

30" - 300" Image size: Arabic, Vietnamese 1.19m-13.11m(100" Throw Distance: STANDARD ACCESSORY

Power Cord: ±40° (Vertical) Keystone:

@3.98m)

VGA cable: Optical Zoom: 1.1x Remote Control: Audible Noise (Eco): 27dB

QSG & CD: QSG: 1 / CD: NA VGA(640 x 480) to Resolution Support:

FullHD(1920 x 1080) Air Filter: **RSPL**

480i, 480p, 576i, HDTV Compatibility: 576p, 720p, 1080i, q080t

Video Compatibility: NTSC, PAL, SECAM

Horizontal Frequency: 15K~102KHz Vertical Scan Rate: 23~120Hz

INPUT

Computer in (D-SUB 15 pin): 2

Composite: Audio-in (3.5mm):

HDMI: 1 (Back)

OUTPUT

Monitor out (D-SUB 15 pin): Audio out (3.5mm):

Speaker: 2W

CONTROL

RS232: USB type mini B (Services):