

LightStream™ WXGA 1280x800 Networkable Projector

True-to-Life Color + Smart Design

PJD6552LW



Featuring true-to-life color and a smart design, the ViewSonic® LightStream PJD6552LW networkable projector makes the grade in any classroom, and helps corporate users rise to the top in any boardroom. Equipped with SuperColor™ technology and a high-brightness output, this projector strikes a perfect balance of color and light to deliver the ultimate in color accuracy without compromise. A smart and intuitive design includes PortAll™—a hidden MHL/HDMI port perfect for wireless dongles (such as the optional ViewSonic WPG-300) that lets you wirelessly stream multimedia content from a mobile device, or notebook PC, to the projector. Designed with an easy-to-use network management system that lets you remotely control over 250 LightStream projectors, the PJD6552LW is great for use in multiple classrooms across an entire campus, or multiple meeting rooms in an office building!

Key Features:

- Best in class color accuracy
- Secure MHL/HDMI port
- Network capable
- Smart design
- Enhanced sound

Designed for:



- Education
- Business
- Home

LightStream™ WXGA 1280x800 Networkable Projector



PJD6552LW

Projection Distance		Screen Size (16:10) Diagonal	
Inches	Meters	Inches	Meters
31-40	0.8-1.0	30	0.8
41-53	1.0-1.4	40	1.0
51-66	1.3-1.7	50	1.3
61-80	1.6-2.0	60	1.5
72-93	1.8-2.4	70	1.8
82-106	2.1-2.7	80	2.0
92-120	2.3-3.0	90	2.3
102-133	2.6-3.4	100	2.5
123-160	3.1-4.1	120	3.0
153-199	3.9-5.1	150	3.8
205-266	5.2-6.8	200	5.1
256-332	6.5-8.4	250	6.4
307-399	7.8-10.1	300	7.6



Specifications

DISPLAY	Type	0.65" Digital Micromirror Device (DLP™)
	Resolution	1280 x 800 (native)
	Lens	1.3x manual optical zoom / manual optical focus
	Keystone	Vertical (± 30°) / Horizontal (± 30°)
	Size	30 – 300 in. / 0.76 – 7.62 m (diagonal)
	Throw Distance	2.6 – 33.3 ft. / 0.78 – 10.14 m
	Throw Ratio	1.21~1.57:1
	Lamp	210 watt
	Light Life	4000 / 10000* (Normal / Eco-mode)
	Brightness	3500 lm
INPUT SIGNAL	Computer and Video	NTSC M(3.58MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM (B, D, G, L, L1), SD 480i and 576i, ED 480p and 576p, HD 720p, 1080i, 1080p
	Frequency	Fh: 15–102KHz, Fv: 23–120Hz
COMPATIBILITY	PC	Up to 1920x1080
	Mac®	Up to 1920x1080 (may require MAC adapter)
CONNECTOR	Digital Input	HDMI 1.4 (x1) / HDMI/MHL (x1)
	RGB Input	15-pin mini D-Sub (x2)
	Composite Input	RCA jack (x1)
	Audio In	3.5mm mini jack (x2)
	Audio Out	3.5mm mini jack (x1)
	Video Out	15-pin mini D-Sub (x1)
	USB	Mini type B (mouse control and maintenance)
	LAN	RJ45
Control	RS232	

AUDIO	Speaker	10W (x1)
NOISE LEVEL	Normal / Eco-mode	32 dB / 27 dB
POWER	Voltage	100~240VAC (Auto Switching), 50-60Hz (universal)
	Consumption	330W (max) / <0.5W (stand-by mode)
CONTROLS	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
	OSD	Display, Picture, Source, System Setup (Basic), System Setup (Advanced), Information (See user guide for full OSD functionality)
OPERATING CONDITIONS	Temperature	32–104° F (0–40° C)
	Humidity	10–90% (non-condensing)
	Altitude	0–6000 ft (1828.8m)
DIMENSIONS (W x H x D)	Physical	12.44 x 8.98 x 4.08 in. / 316 x 228 x 103.7 mm
	Packaging	16.0 x 17.72 x 8.85 in. / 410 x 450 x 225 mm
WEIGHT	Net	5.1 lb. / 2.3 kg
	Gross	8.8 lb. / 4.0 kg
REGULATIONS		CB, TUV-GS, UL/cUL, FCC (including ICES-003), CE, C-Tick, Mexico Energy test/Registration, EAC, UkrSEPRO/EMC DOC, UL COC, TUV- Mark (Argentina), PSB, KCC, KC, SASO, CCC, WEEE, RoHS, REACH, SVHC, ErP
WARRANTY		3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service**

Optional Accessories (Sold Separately)

Wireless Presentation Gateway Dongle.....	WPG-300
3D Active Shutter Glasses.....	PGD-350
Ceiling Mount.....	WMK-005
Carrying Case.....	PJ-CASE-008
Replacement Lamp.....	RLC-098
Cable Management.....	PJ-CM-002
Extended Warranty.....	PJ-EW-07-02

What's in the box?

PJD6552LW projector, power cable, VGA cable, remote control with laser (batteries included), Quick Start Guide, ViewSonic Wizard CD (with User Guide)



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

*Lamp life may vary based on actual usage and other factors. **One year Express Exchange® service requires product registration. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies, DLP® and DLP logo are registered trademarks of Texas Instruments. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Copyright © 2016 ViewSonic Corporation. All rights reserved. [18470-00B-01/16]

www.viewsonic.com